

	IP63	IP65 (new)
		
Physical	<p>Size: 134 x 53 x 26 mm Colour: Black Display: CSTN, more than 65000 colours 28 x 35 mm 128 x 160 pixel White LED backlight</p>	<p>Size: 137 x 52 x 21.5 mm Colour: Black Display: TFT 31 x 41 mm 240 x 320 pixel White LED backlight</p>
Buttons & Keys	<p>3 function keys On hook, power on / hook off 4 direction navigation Numeric block Volume + and - Ringtone on / off</p>	<p>3 function keys On hook, power on / hook off 4 direction navigation Numeric block Volume + and - Ringtone on / off</p>
Battery	<p>Type: Li-polymer Speech time: 20 h Charge time: <4 h</p>	<p>Type: Li-polymer Speech time without Bluetooth headset: 20 h Speech time with Bluetooth headset: 13 h Charge time: <4 h</p>
Interfaces	<p>Headset interface (Standard 2.5 mm) Bluetooth</p>	<p>Headset interface (Standard 3.5 mm) Bluetooth</p>
Radio	<p>Frequency range: 1880-1900 MHz Modulation: GFSK Antenna: Integral Sensitivity: -93 dBm Dynamic output power: 10 mW (EU)</p>	<p>Frequency range: 1880-1900 MHz Modulation: GFSK Antenna: Integral Sensitivity: -93 dBm Dynamic output power: 10 mW (EU)</p>
Environmental	<p>Operating temperature: 0°C to +40°C Storage temperature: -20°C to +60°C Enclosure protection: IP44</p>	<p>Operating temperature: 0°C to +40°C Storage temperature: -20°C to +60°C Enclosure protection: IP44, IEC EN60529</p>
Order number	50-00063-001	50-00065-001