

Vacuum Conveyor VTEC 200..

- Supply air pressure** : 4–6 bar (Max 7 bar) [58–87 psi]
Air consumption : 600–780 NI/m [21.18–27.54 scfm]
Noise level : 68–76 dBA
Steel Material : SUS304 / SUS 316L
Sealing Material : Silicone
Filter Material : • TFE coated antistatic needle felt of polyester / carbon fibers
 • Washable 2 to 4 times in 40°C
 • Food quality
Working temp. : -20°C to +80°C



Ordering information

Model	Vacuum pump	Power requirement (Pr)	Filter surface (dm ²)	Control	Fluidization
VTEC 200-AC	VTM200 C	5-10	14	Pneumatic	-
VTEC 200-AC 2		5-10	14	Pneumatic	-
VTEC 200-AC B		5-10	14	Pneumatic	Attached
VTEC 200-EC (A)*		5-10	14	Electric	-
VTEC 200-EC B(A)*		5-10	14	Electric	Attached
VTEC 200L-AC		5-10	26	Pneumatic	-
VTEC 200L-AC 2		5-10	26	Pneumatic	-
VTEC 200L-AC B		5-10	26	Pneumatic	Attached
VTEC 200L-EC (A)*		5-10	26	Electric	-
VTEC 200L-EC B(A)*		5-10	26	Electric	Attached

*..(A) : With Injection valve ⇨ See page 03

Difference between '...-AC' and '...-AC2' ⇨ See page 12

Model	Max. Conveying capacity (ton)	Capacity ton/h at different conveying distance				Rec.Material pipe dimension (mm)	Recommended material volume (ℓ/cyle)	Weight (kg)
		5m	10m	20m	30m			
VTEC 200-AC	1.5	1.5	0.8	0.4	0.2	32 / 40 / 50	4	19.4
VTEC 200-AC 2	1.5	1.5	0.8	0.4	0.2	32 / 40 / 50	4	19.2
VTEC 200-AC B	1.5	1.5	0.8	0.4	0.2	32 / 40 / 50	4	19.7
VTEC 200-EC (A)*	1.5	1.5	0.8	0.4	0.2	32 / 40 / 50	4	22.9
VTEC 200-EC B(A)*	1.5	1.5	0.8	0.4	0.2	32 / 40 / 50	4	23.2
VTEC 200L-AC	1.5	1.5	0.8	0.4	0.2	32 / 40 / 50	4	20.8
VTEC 200L-AC 2	1.5	1.5	0.8	0.4	0.2	32 / 40 / 50	4	20.6
VTEC 200L-AC B	1.5	1.5	0.8	0.4	0.2	32 / 40 / 50	4	21.1
VTEC 200L-EC (A)*	1.5	1.5	0.8	0.4	0.2	32 / 40 / 50	4	23.7
VTEC 200L-EC B(A)*	1.5	1.5	0.8	0.4	0.2	32 / 40 / 50	4	24

*..(A) : With Injection valve ⇨ See page 03